



Providing quality and
reliability since 1958

HotShot MegaX3cc

1280 x 1024 up to 1000 frames per second (fps)



HotShot MegaX3 CC Features

CMOS Sensor

1280 X 1024 @ 1000fps
all Active Pixels

Bit Depth

10 - bit

Adjustable Electronic Shutter

down to 2us

GigaBit Ethernet Interface

Lens Mount

C-Mount OR F-Mount supporting "G type"

Compact Housing

145 x 95 x 78mm

Synchronisation

Internal and external sync recording

Simple Intuitive Control Software

Including Auto Tracking Function to
measure, Acceleration, Velocity and
Displacement

Light Sensitivity

ISO 1500 Mono
ISO 500 Colour

Power

12VDC / 12W



NAC Deutschland GmbH
Hedelfingerstr. 54-70
70327 Stuttgart
Germany
Tel: +49 (0)711 2201 885
E-mail: rwestphal@nacinc.de
www.nacinc.eu

HotShot MegaX3 CC

High Speed Camera System

Frame Rate	Available Resolution (examples)		Record Time Sec (8 bit)			
	FPS	Hor.	Vert.		8GB	16GB
100	1280	1024			64.09	128.17
250	1280	1024			25.63	51.27
500	1280	1024			12.82	25.63
1,000	1280	1024			6.41	12.82
1,500	1280	720			6.08	12.15
2,000	800	600			8.75	17.50
4,000	600	400			8.75	17.50
6,000	400	300			11.67	23.33
8,000	384	256			10.68	21.36
10,000	320	200			13.13	26.25
20,000	160	100			26.25	52.50

The above are some common format examples

* Note: Recording Time Depends on Memory Configuration, Resolution, Frame Rate and Image Bit Depth.

Recording Time (seconds) = [(Memory Configuration X 1024 X 1,000,000) / (Bytes/Frame)] / (Frames/Second)
Bytes/Frame= (Horizontal pixels X Vertical Pixels X Bit Depth/8)



NAC Deutschland GmbH
Hedelfingerstr. 54-70
70327 Stuttgart
Germany
Tel: +49 (0)711 2201 885
E-mail: rwestphal@nacinc.de
www.nacinc.eu