

# MEMRECAM HX-5

High Speed Camera System

2560 x 1920 up to 1,370 frames per second (fps)

HX5 : Full Performance

HX5E : Limited in Frame Rate and Shutter Speed



## Memrecam HX-5 Features

### CMOS Sensor

2560 X 1920 - all Active Pixels

### Bit Depth

12/10/8-bit (selectable)

### Adjustable Electronic Shutter

Minimum HX5E 1.1 $\mu$ s ; HX5 : 300ns

### Adjustable Frame Rates

in 1fps steps

### Adjustable Resolution

### Variable Framing Profile

a variety of frame rates in one recording sequence

### Multiple Trigger Modes

Burst, multi-trigger, restart-trigger and image trigger

### Sync

High resolution timing and sync to < 73ns

### Straddle Mode

Inter-frame time for PIV applications = 182ns

### Memory Segmentation

### Dual Segment Recording

Simultaneously record to two separate memory segments at two different recording speeds

### High Light Sensitivity

ISO 2500 (colour) ISO 10,000 (mono)

### Ultra High Sensitivity in Super Pixel Mode (2x2)

ISO 10,000 (colour) ISO 40,000 (mono)

### Sealed Core

protects against dust, sand, dirt, etc. for use in dirty environments

### Auto Exposure Control

### Automatic Temperature Calibration

### Ultra-Fast Gig-E Interface

### Fast Download

to USB 2.0 HDD

### Continuous Live Video Output

### Stand alone control

no PC required

### Memory Backup Battery

### Dynamic Range Expansion Shutter

### IRIG-B Capture & Sync with Phase Shift

### Compact Design

5.5kg -110W x 140H x 333D(mm)



# MEMRECAM HX-5

## High Speed Camera System



Frame Rate	Available Resolution (examples)		Record Time Sec (8 bit)		
	FPS	Hor.	Vert.	16GB	32GB
100	2560	1920	34.18	68.36	136.72
250	2560	1920	13.67	27.34	54.69
500	2560	1920	6.84	13.67	27.34
1,000	2560	1920	3.42	6.84	13.67
1,300	2560	1920	2.63	5.26	10.52
2,000	2048	1600	2.56	5.13	10.25
2,700	1920	1280	2.53	5.06	10.13
3,200	1920	1080	2.53	5.06	10.13
4,000	1600	1024	2.56	5.13	10.25
5,000	1280	1016	2.58	5.17	10.33
6,000	1280	840	2.60	5.21	10.42
6,000	1024	1024	2.67	5.34	10.68
7,000	1280	720	2.60	5.21	10.42
7,500	1024	824	2.65	5.31	10.62
8,000	1024	776	2.64	5.29	10.57
10,000	896	696	2.69	5.39	10.78
15,000	768	528	2.76	5.52	11.05
20,000	640	464	2.83	5.66	11.31
30,000	512	376	2.91	5.82	11.64
40,000	512	296	2.77	5.54	11.09
50,000	448	264	2.84	5.68	11.36
75,000	384	192	3.04	6.08	12.15
100,000	384	144	3.04	6.08	12.15
200,000	320	72	3.65	7.29	14.58
210,000	320	64	3.94	7.88	15.76
Below is HX5 Model ONLY					
300,000	320	48	3.65	7.29	14.58
416,000	320	32	3.94	7.89	15.78
500,000	320	24	4.38	8.75	17.50
650,000	320	16	5.05	10.10	20.19
916,500	320	8	7.16	14.32	28.64

The above are some common format examples

\* Note: Recording Time Depends on Memory Configuration, Resolution, Frame Rate and Image Bit Depth.

Recording Time (seconds) = [(Memory Configuration X 1024 X 1,000,000) / (Bytes/Frame)] / (Frames/Second)

Bytes/Frame= (Horizontal pixels X Vertical Pixels X Bit Depth/8)

Model HX5 requires Export Licence

Specification Subject to change



NAC Deutschland GmbH  
Hedelfingerstr. 54-70  
70327 Stuttgart  
Germany  
Tel: +49 (0)711 2201 885  
E-mail: rwestphal@nacinc.de  
www.nacinc.eu

NAC Image Technology  
1 Beach Street  
Dawlish, Devon  
EX7 9PN, UK  
Tel: +44 (0)1626 867777  
E-mail: jimmy.robinson@nacinc.com  
www.nacinc.co.uk