

Memrecam GX-5 Camera Head Options

P-Cam (25 x 25 x 95mm) - The P-Cam is a small micro head camera designed for poorly illuminated or otherwise inaccessible spaces and is available in five (5) different configurations:

- Straight head, Straight Connector
- Straight Head, Angled Connector
- Angled Head, Straight Connector
- Angled Head, Angled Connector
- Angled Head, Return-angled Connector



SS



SA



AS



AA



AR



S-Cam (25 x 25 x 25mm) - The S-Cam has the sensor separated from the camera head in order to reach even smaller, more confined spaces and is available in either a straight or angled head.

HR-Cam - The HR-Cam is a high resolution ultra light sensitive, tethered head camera (color: ISO 5,000, monochrome: ISO 20,000) capable of recording images at 1280 x 960 at 1,000 fps. The HR-Cam is available in either an F-Mount or an M-Mount.



A **Booster Unit BB1** is an optional accessory item that can extend the distance between the Camera Head and the DRP up to a maximum of 18 meters! (pictured below with P-Cam and cable)



* Extension Cables are available in lengths of 4, 6 and 8 meters.



Contact Us in the Americas:

NAC Image Technology
15 McCoy Place
Simi Valley, CA 93065
Tel: +1 805-584-8862
Email: sales@nacinc.com

Contact Us in Europe:

NAC Deutschland GmbH
Hedelfingerstr. 54-70
70327 Stuttgart, Germany
Tel: +49(0)711 2201 885
E-mail: rwestphal@nacinc.de

Contact Us in Asia:

NAC Image Technology Inc.
2-11-3 Kita-Aoyama, Minato-ku
Tokyo 107-0061 Japan
Tel: +81 3 3796 7903
Email: nacinternational@camnac.co.jp

Visit our website at www.nacinc.com